

# oilfino Via Eco GF 0W-20



## DESCRIPTION

**oilfino Via Eco GF 0W-20** is a fuel-efficient high-performance engine oil, particularly developed for modern passenger car petrol engines, e.g. hybrid vehicles and those which set special focus on high fuel savings and reduction of CO2 emissions. oilfino Via Eco GF 0W-20 is appropriate for usage throughout the year even at very low temperature and an ideal solution for downsizing engines with automatic start/stop.

## PROPERTIES

- Fuel savings up to 3.1% - tested in the official ILSAC Engine Test Seq. VI D
- exceptional flowability at very low temperature - safe cold start
- ensures compliance with EURO standards concerning pollutant load
- better protection of the TWC (three way catalytic converter) due to optimised formulation

## SPECIFICATIONS

- API SP

## PERFORMANCE LEVEL

- ILSAC GF-5
- dexos1 (First Generation)
- Fiat 9.55535-GSX/CR1
- Ford WSS-M2C947-A
- Chrysler MS-6395
- GM 6094M

## RECOMMENDED FOR

- Asian manufacturers such as TOYOTA (petrol engines from May 2009), HONDA and MITSUBISHI, recommending SAE 0W-20.

Specifications	Method	Unit	oilfino Via Eco GF 0W-20
SAE grade	SAE J 300		0W-20
Density at 15°C	D 4052	kg/m <sup>3</sup>	849
Viscosity at 40°C	DIN 51562	mm <sup>2</sup> /s	47,2
Viscosity at 100°C	DIN 51562	mm <sup>2</sup> /s	8,7
Viscosity index	DIN ISO 2909		167
Pour point	DIN ISO 3016	°C	-42

*Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.*