



DESCRIPTION

oilfino Antifreeze is an ethylene glycol based radiator corrosion inhibitor and antifreeze concentrate for engines cooled by water.

PROPERTIES

oilfino Antifreeze offers excellent protection against corrosion and is recommended for cast iron or aluminium engines (or a combination of the two) along with aluminium and copper alloyed radiator systems.

oilfino Antifreeze's low evaporation properties combined with impressive protection from corrosion, rust and cavitation as well as a long service life with reliable antifreeze protection make it the ideal year-round product for radiator systems. It does not contain nitrite, amine or phosphate, making it more environmentally compatible.

PROTECTION AGAINST CORROSION AND FROST

oilfino Antifreeze provides year-round protection against corrosion and frost. oilfino Antifreeze provides optimal protection in a 50:50 mixing ratio in volume % with solely demineralised or distilled water. oilfino Antifreeze concentrate needs to be diluted with water prior to use and may only be used in concentrations of min. 33 vol. % to max. 60 vol. %.

SPECIFICATIONS

- BS 6580:2010
- ASTM D3306
- ASTM D1384
- AFNOR NF R 15-601 NOV 2020
- SAE J1034

NOTE

Antifreeze does not contain silicate, borate, 2-ethylhexanoic acid, nitrite, amine or phosphate.

Specific data	Method	Unit	oilfino Antifreeze
Colour	Visual	-	Blue
Density at 20°C	D4052	g/ml	1.110-1.140
pH value (50 vol. %)	D 1287		8.4
Crystallisation point (50 vol. %)	D 1177	°C	-37
Nitrites, amines, phosphates			None

All information is provided to the best of our knowledge but without guarantee of any kind. The technical data represent average values and are subject to normal production fluctuations. oilfino reserves the right to improve the products and modify the specification accordingly.