



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.07.2021

Version number 2.8

Revision: 13.07.2021

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- **Product identifier**
- **Trade name: Oilfino Varius G 620 75W-90**
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Lubricating oil
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
oilfino Mineralöl GmbH
Werkstr. 12
D- 25497 Prisdorf
info@oilfino.com
Tel.: +49 (0) 4101 / 79900
www.oilfino.com
- **Further information obtainable from:** Sales
- **Emergency telephone number:**
Gift-Informationszentrum Nord (Göttingen)
Telefon +49 (0)551-19240

SECTION 2: Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.
- **Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms** Void
- **Signal word** Void
- **Hazard statements**
H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements**
P273 Avoid release to the environment.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Additional information:**
EUH 208: Contains Amine, C10-14-tert-Alkyl. May produce an allergic reaction.
- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.

(Contd. on page 2)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.07.2021

Version number 2.8

Revision: 13.07.2021

Trade name: Oilfino Varius G 620 75W-90

(Contd. of page 1)

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 157707-86-3	1-decene, trimer, hydrogenated Asp. Tox. 1, H304	≥25-≤100%
CAS: 1213789-63-9 EC number: 627-034-4	C16-18- (geradzahlige, gesättigte und ungesättigte) Alkylamine STOT RE 2, H373; Asp. Tox. 1, H304; Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; STOT SE 3, H335	≥0.025-<0.25%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **Description of first aid measures**
- **After skin contact:** If skin irritation continues, consult a doctor.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:** Symptomatic treatment
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 3)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.07.2021

Version number 2.8

Revision: 13.07.2021

Trade name: Oilfino Varius G 620 75W-90

(Contd. of page 2)

- **Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about fire - and explosion protection:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **Storage class (TRGS):** 6.1 D
- **Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 4)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.07.2021

Version number 2.8

Revision: 13.07.2021

Trade name: Oilfino Varius G 620 75W-90

(Contd. of page 3)

· Control parameters**· Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs**1213789-63-9 C16-18- (geradzahlige, gesättigte und ungesättigte) Alkylamine**

Inhalative	DNEL long-term - inhalation local effects	1 mg/m ³ (Worker)
	DNEL Long-term – inhalation, systemic effects	0.38 mg/m ³ /day (Worker)
	DNEL Acute - inhalation, local effects	1 mg/m ³ (Worker)

· PNECs**1213789-63-9 C16-18- (geradzahlige, gesättigte und ungesättigte) Alkylamine**

PNEC short term, fresh water	0.000026 mg/l (Aquatic organisms)
PNEC short term, sea water	0.0000026 mg/l (Aquatic organisms)
PNEC short term fresh water sediment	3.76 mg/kg (Aquatic organisms)
PNEC short term soil	10 mg/kg (terrestrial organisms)
PNEC short term sea water sediment	0.376 mg/kg (Aquatic organisms)

· **Additional information:** The lists valid during the making were used as basis.

· Exposure controls**· Personal protective equipment:**

· **General protective and hygienic measures:** Wash hands before breaks and at the end of work.

· **Respiratory protection:** Not required.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.07.2021

Version number 2.8

Revision: 13.07.2021

Trade name: Oilfino Varius G 620 75W-90

(Contd. of page 4)

· **Eye protection:** Goggles recommended during refilling**SECTION 9: Physical and chemical properties**· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**

· Form:	Fluid
· Colour:	Yellowish
· Odour:	Characteristic
· Odour threshold:	Not determined.

· **pH-value at 20 °C:** 7.5-9· **Change in condition**

· Melting point/freezing point:	-57 °C
· Initial boiling point and boiling range:	226 °C

· **Flash point:** Not applicable.· **Flammability (solid, gas):** Not applicable.· **Decomposition temperature:** Not determined.· **Auto-ignition temperature:** Product is not selfigniting.· **Explosive properties:** Product does not present an explosion hazard.· **Explosion limits:**

· Lower:	Not determined.
· Upper:	Not determined.

· **Vapour pressure:** Not determined.

· Density at 20 °C:	0.864 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.

· **Solubility in / Miscibility with water:** Not miscible or difficult to mix.· **Partition coefficient: n-octanol/water:** Not determined.

(Contd. on page 6)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.07.2021

Version number 2.8

Revision: 13.07.2021

Trade name: Oilfino Varius G 620 75W-90

(Contd. of page 5)

· Viscosity:	
Dynamic:	Not determined.
Kinematic at 40 °C:	97 mm ² /s
· Solvent content:	
VOC (EC)	0.00 %
Solids content:	0.0 %
· Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:**157707-86-3 1-decene, trimer, hydrogenated**

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)

1213789-63-9 C16-18- (geradzahlige, gesättigte und ungesättigte) Alkylamine

Oral	LD50	>1,200 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.

(Contd. on page 7)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.07.2021

Version number 2.8

Revision: 13.07.2021

Trade name: Oilfino Varius G 620 75W-90

(Contd. of page 6)

- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· **Toxicity**

· **Aquatic toxicity:**

157707-86-3 1-decene, trimer, hydrogenated

Inhalative	LC50 (4h)	>5 mg/l (rat)
------------	-----------	---------------

1213789-63-9 C16-18- (geradzahlige, gesättigte und ungesättigte) Alkylamine

LC50 (96h) mg/ltr.	>0.84 mg/ltr (Fish, minnows)
EC50 (48h)	0.32 mg/l (daphnia)
EC50 (72h)	>0.39 mg/l (algae)
NOEC	0.63 mg/ml /4d (Fish)

- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

· **Ecotoxicological effects:**

· **Remark:** Harmful to fish

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 8)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.07.2021

Version number 2.8

Revision: 13.07.2021

Trade name: Oilfino Varius G 620 75W-90


(Contd. of page 7)

- **Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **UN-Number**
- **ADR, IMDG, IATA** UN3287
- **UN proper shipping name**
- **ADR** 3287 TOXIC LIQUID, INORGANIC, N.O.S. (Amine, C10-14-tert-Alkyl)
- **IMDG, IATA** TOXIC LIQUID, INORGANIC, N.O.S. (Amine, C10-14-tert-Alkyl)
- **Transport hazard class(es)**
- **ADR, IMDG, IATA**

- **Class** 6.1 Toxic substances.
- **Label** 6.1
- **Packing group**
- **ADR, IMDG, IATA** III
- **Environmental hazards:** Not applicable.
- **Special precautions for user** Warning: Toxic substances.
- **Hazard identification number (Kemler code):** 60

(Contd. on page 9)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.07.2021

Version number 2.8

Revision: 13.07.2021

Trade name: Oilfino Varius G 620 75W-90

(Contd. of page 8)

· EMS Number:	F-A,S-A
· Stowage Category	A
· Stowage Code	SW2 Clear of living quarters.
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	2
· Tunnel restriction code	E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3287 TOXIC LIQUID, INORGANIC, N.O.S. (AMINE, C10-14-TERT-ALKYL), 6.1, III

SECTION 15: Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **National regulations:**
- **VOC (EU) 0.0 g/l**
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

GB

(Contd. on page 10)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.07.2021

Version number 2.8

Revision: 13.07.2021

Trade name: Oilfino Varius G 620 75W-90

(Contd. of page 9)

SECTION 16: Other information

Disclaimer

This safety data sheet contains only safety relevant information. The information is based on the state of our knowledge at the time of revision, however, it does not constitute a guarantee of product properties, product information or product specifications and does not establish a contractual legal relationship. This document is only valid in its unchanged form. In the event of changes by third parties, the exhibitor accepts no responsibility for form and content or for any damages or claims arising from such changes. The information is not transferable to other products. If the product named in this safety data sheet is mixed, blended or processed with other materials or is subjected to processing, the information in this safety data sheet cannot be transferred to the new material produced in this way, unless expressly stated otherwise. The data sheet does not release the user from the obligation to ensure that he acts in accordance with all regulations in connection with his activity.

Relevant phrases

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Department issuing SDS: Quality Management department**Contact:** MSDS authorized Person**Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

(Contd. on page 11)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.07.2021

Version number 2.8

Revision: 13.07.2021

Trade name: Oilfino Varius G 620 75W-90

(Contd. of page 10)

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
· *** Data compared to the previous version altered.**

GB