

Cultor M 15W-40



DESCRIPTION

oilfino Cultor M 15W-40 An up-to-date multifunctional lubricating oil for agricultural- and earthmoving equipment, formulated with top-grade solvent refined base oils and additives, to achieve the following properties:

- a powerful dispersion and detergency
- a high activity against wear, corrosion and foam
- a very strong resistance to oxidation
- an excellent extreme pressure properties
- a high and stable viscosity index

PROPERTIES

This multifunctional lubricant () has been developed to achieve one single lubricating oil that is able to lubricate:*

- gasoline engines
- diesel engines (with or without turbo-charging)
- transmissions (also „wet“ brakes)
- hydraulic systems

() a so-called Super Tractor Oil Universal = STOU*

SPECIFICATIONS

- SAE 15W-40
- ACEA E3
- API SF/CG-4
- API GL-4

PERFORMANCE LEVEL

- STOU
- MIL-L 2104D
- John Deere J27C
- Massey Ferguson CMS M1143/M1144/ M1145
- MB 227.1
- ZF TE-ML 06B/07B
- Allison C-4
- Caterpillar TO-2
- Ford M2C134-D

Specific Data	Method	Unit	oilfino Cultor M 15W-40
Density at 15°C	DIN 51757	kg/l	0,874
Dynamic viscosity at -20°C	ASTM D 5293	mPA s	4760
Viscosity at 40 °C	DIN EN ISO 3104	mm ² /s	93,50
Viscosity at 100 °C	DIN EN ISO 3104	mm ² /s	14,50
Viscosity index	DIN ISO 2909		137
Flash point COC	DIN ISO 2592	°C	218
Pour point	DIN ISO 3016	°C	-36
Base number	DIN ISO 3771	mgKOH/g	10,7
Sulfate ash content		%	1,45

Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.