#### **PRODUCT INFORMATION**

# oilfino Cultor T 10W-40



#### DESCRIPTION

**oilfino Cultor T** is a semi-synthetic multi-purpose tractor oil (STOU) for engines, transmissions, hydraulics and transmission/hydraulic systems with and without integrated wet brakes for uniform supply of agricultural and construction vehicles. Diversely using this product as multigrade engine oil and transmission / hydraulic oil leads to reduction of storage and handling costs.

### PROPERTIES

With its excellent low temperature properties oilfino Cultor T ensures an immediate response of the hydraulic systems at low outside temperature and great lubrication during power transmission with extreme loads. It prevents IPTO clutches from slipping and the frictional behaviour has been adjusted to the special requirements of "wet brakes" running in an oil bath. Viscosity 10W-40 secures all-season supply and good cold start performance of engines and hydraulics.

#### SPECIFICATION

- SAE 10W40
- ACEA E3

• API SF/CG-4

ACEA E3

• API GL-4

### PERFORMANCE LEVEL

- STOU
- ZF TE-ML 06B/07B/06F
- John Deere JDM J20C/J20D/J27
- Ford M2C 86B/C, 134D, 159B/C
- Case MS 1204, 1206, 1207, 1209
- CNH MAT 3525, 3526
- Massey Ferguson MF CMS M1135/M1139/
- M1143/M1144/M1145

- MB 227.1
- Fendt Vario
- Allison C-4
- Caterpillar TO-2
- Sperry Vickers Eaton I-280-S, Eaton
- M2950S
- Sauer Sunstrand Danfoss Hydrostatic
- Trans Fluid

| Specific Data      | Method       | Unit    | oilfino Cultor T 10W-40 |
|--------------------|--------------|---------|-------------------------|
| SAE grade          | SAE J 300    |         | 10W-40                  |
| Density at 15°C    | DIN 51757    | kg/m³   | 867                     |
| Viscosity at -25°C | DIN 51377    | mPAs    | 6310                    |
| Viscosity at 40°C  | DIN 51562    | mm²/s   | 86,4                    |
| Viscosity at 100°C | DIN 51562    | mm²/s   | 13,2                    |
| Viscosity index    | DIN ISO 2909 |         | 153                     |
| Flash point        | DIN ISO 2592 | °C      | 234                     |
| Pour point         | DIN ISO 3016 | °C      | -42                     |
| Base number        | DIN ISO 3771 | mgKOH/g | 11,0                    |
| Sulphate ash       | DIN 51575    | g/100g  | 1,4                     |

Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.

## oilfino.com