

oilfino Cultor Utto



DESCRIPTION

oilfino Cultor Utto is a universal transmission / hydraulic oil for supply of agricultural and construction vehicles with a common oil circuit for transmission / axle drive and hydraulics.

PROPERTIES

oilfino Cultor Utto ensures an immediate response of the hydraulic systems at low outside temperature and great lubrication during power transmission with extreme loads. It prevents IPTO clutches from slipping and the frictional behaviour has been adjusted to the special requirements of „wet brakes“ running in an oil bath. oilfino Cultor Utto not only meets but also exceeds specifications of well-known tractor manufacturers and can easily be used with the specifications listed below.

SPECIFICATION

- SAE 10W-30; ISO VG 68
- API GL-4

PERFORMANCE LEVEL

- UTTO
- Massey Ferguson CMS M1135/M1141/ M1143/M1145
- Valtra G2-08
- Case MS 1206/1207/1209
- CNH MAT 3505/3509/3525/3540
- Ford M2C 134D
- FNHA 2C 201.0
- John Deere JDM J20C
- Volvo CE WB 101
- New Holland NH 410B / NH 410C
- Claas
- Renault Agriculture
- McCormick HTX
- AGCO/Allis 821 XL
- Kubota UDT
- ZF TE-ML 03E/ 05F/ 06P/ 17E/ 21F

Specific Data	Method	Unit	oilfino Cultor UTTO
SAE grade	DIN 51511		70W-85 / 10W-30
Density at 15°C	D 4052	kg/m ³	887
Viscosity at 40°C	DIN 51562	mm ² /s	59
Viscosity at 100°C	DIN 51562	mm ² /s	10,1
Viscosity index	DIN ISO 2909		161
Flash point	DIN ISO 2592	°C	225
Pour point	DIN ISO 3016	°C	-39

Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.