

oilfino Sponte ATF VI



DESCRIPTION

oilfino Sponte ATF VI is an automatic transmission oil based on synthetic technology which meets requirements of General Motors Dexron VI specifications. Due to its specific formulation, it is also applicable for former Dexron II and Dexron III specifications. This high-quality oil for automatic transmissions (ATF) can be used in automatic transmissions with torque converters of passenger cars as well as in oil bath clutches and power steering systems.

PROPERTIES

oilfino Sponte ATF VI offers

- very high shifting comfort, no vibrations
- excellent wear protection and thus a significantly extended transmission service life
- excellent temperature and oxidation stability

PERFORMANCE LEVELS

- Aisin Warner JWS 3309, JWS 3324, AW-1
- Audi 5 HP LT 71141
- Audi / VW G 052 025-A2, G 053 025-A2
- Audi / VW G 052 162-A1/A2, G 055 025-A2
- Audi / VW G 052 162, G 055 162-A2, -A6
- Audi / VW G 060 162, G 052 990
- Audi / VW G 055 540 (A2), G 052 055
- BMW JWS 3309 (T-IV), LA 2634, LT 71141
- BMW 7045E, ETL 8072B, M 1375.4
- BMW ZF 5HP18FL, 5HP24, 5HP30
- BMW Mini / Mini Cooper T-IV
- Chrysler ATF+, +2, +3
- Fiat T-IV Typ, JWS 3309
- Ford Mercon, FNR5
- Ford M2C138-CJ, M2C166-H
- Ford WSS M2C 922 A1, 924 A (XT-8-QAW)
- Honda ATF 3.1, DW-1
- Hyundai / KIA SP-IV-M
- Isuzu BESCO ATF-II, ATF-III
- Jaguar ATF 3403 M115, JLM 20238
- Jaguar LT 71141, ZF 5HP 24
- Kia SP-II, SP-III, SP-IV, SP-IVM, Red 1
- Mazda ATF D-II, M-III, M-V, FZ
- Mazda F-1, S-1, N-1
- Mitsubishi Diaqueen ATF-PA
- Nissan Matic Fluid S
- Opel / GM 19 40 700, 19 40 767
- Opel / GM 21005966 Transaxle
- Opel / GM 2217466, 889200925, 9986195
- Peugeot ZF 4HP20
- Peugeot / Citroen Z 000169756
- Peugeot / Citroen (PSA) AL4
- Porsche ATF 3403 M115
- Porsche 000 043 205 09, -28
- Porsche 99917 547 00 (A2)
- Porsche Z 000196756
- Subaru ATF, 5AT, HP
- Suzuki ATF 2326, 2384 K
- Suzuki ATF 3309, 3314, 3317
- Toyota ATF D-II, D-III
- Toyota ATF T-III, T-IV, WS
- Voith 55.6336.XX (G607)
- Volvo CE 97340
- Volvo 97325, 97335
- Volvo PN 116 1521, -1540
- Volvo PN 116 1640, - 1621
- VW 5 HP (ZF 5 HP 30)
- VW 5 HP (18FL, 19FL, 24A, 30)
- VW TL 521 61
- VWGUS000162
- ZF 3&4 speed Transmissions
- ZF 8 speed Transmissions
- ZF 9 speed Transmissions
- ZF TE-ML 09, 11A, 11B, 21L

Specific Data	Method	Unit	oilfino Sponte ATF VI
Colour			Red
Density at 15°C	DIN 51757	kg/m ³	843
Kinematic viscosity at 40°C	DIN 51562	mm ² /s	30
Kinematic viscosity at 100°C	DIN 51562	mm ² /s	6,0
Viscosity index	D 2270		151
Dynamic viscosity at -40°C	ASTM D2983	mPa.s	13.400
Pour point	DIN ISO 3016	°C	-51

Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.