

oilfino Varius G 400 LS



DESCRIPTION

Hypoid gear oils for drive axles with self-locking differential. It contains specific additives for limited slip and it prevents noise at highest mechanical and thermal loads.

PROPERTIES

Selected base oils combined with appropriate additive technology ensure very good flowability at low temperatures and great lubrication at high operating temperatures. Lubrication is ensured by excellent wear protection even under highest mechanical permanent or shock loads.

SPECIFICATION

- API GL-5 / LS

APPROVAL

- ZF TE-ML 05C, 12C, 16E, 21C

PERFORMANCE LEVEL

- MIL-L-2105 B/C/D
- Ford M2C 104A

Specific Data	Method	Unit	oilfino Varius G 400 LS
SAE grade	DIN 51512		85W-90
Density at 15°C	DIN 51757	kg/m ³	902
Kinematic viscosity at 40°C	DIN 51562	mm ² /s	215
Kinematic viscosity at 100°C	DIN 51562	mm ² /s	17,8
Viscosity index	D 2270		90
Flash point	DIN ISO 2592	°C	205
Pour point	DIN ISO 3016	°C	-21

Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.