

oilfino Varius G 550



DESCRIPTION

oilfino Varius G 550 are high quality hypoid gear oils for highly stressed hypoid toothed drive axles of cars and commercial vehicles.

PROPERTIES

oilfino Varius G 550 offers excellent wear protection and excellent oxidation and temperature stability even with extreme operation and toughest conditions. The selected base oils with the appropriate additive technology guarantee on every good flow behavior at low temperatures and high lubrication safety at high operating temperatures.

SPECIFICATIONS

- API GL-4/GL-5/MT-1

PERFORMANCE LEVEL

- MIL-PRF-2105 D/E
- MB 325.0
- MAN 341 Z2, MAN 342 M2
- ZF TE-ML 02B, 05A, 12L, 12M, 16B, 17H, 19B, 21A
- Scania STO 1:0
- Robert Bosch TE ML 08
- Ford M2C197-A
- Mack GO-J
- Arvin Meritor Transmission 076-D
- Volvo 97321
- DAF
- Iveco

Specific Data	Method	Unit	oilfino Varius G 550
SAE grade	SAE J 306		80W-90
Density at 15°C	DIN 51757	kg/m ³	898
Dynamic viscosity at -26°	DIN 51377	mPas	130.000
Kinematic viscosity at 40 °C	DIN 51398	mm ² /s	139
Kinematic viscosity at 100 °C	DIN 51398	mm ² /s	14,1
Flash point COC	DIN ISO 2592	°C	220
Pour point	DIN ISO 3016	°C	-27
FZG-exam A/8.3/90	DIN ISO 14635		>12

Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.