

# oilfino Via Eco 0W16



## BESCHREIBUNG

**oilfino VIA ECO 0W16** is a synthetic low-friction engine oil for passenger car petrol and diesel engines with and without turbocharging and direct injection. Oilfino Via Eco 0W-16 is characterized by excellent cold start properties, minimization of fuel consumption, friction and wear. Extended oil change intervals according to the manufacturer's instructions.

It is ideally suited for energy-saving year-round use in all modern passenger car gasoline and diesel engines. It thus reduces CO2 emissions and helps protect the environment. Oilfino Via Eco 0W-16 is used in engines with the specified specifications. The operating regulations of the vehicle and engine manufacturers must be observed.

## PROPERTIES

- Excellent cold start properties even at low temperatures
- An extremely stable and excellent viscosity behavior, shear stability
- Fuel savings under all operating conditions
- Very good detergent and dispersing properties
- Neutrality towards sealing materials
- Low evaporation tendency, therefore low oil consumption
- Excellent protection against wear, corrosion and foam formation.
- Catalyst suitability
- Extended oil change intervals protect natural resources

## SPECIFICATIONS

- API SP (RC)
- ILSAC GF-6B

Specific Data	Method	Unit	oilfino VIA ECO 0W16
SAE class	DIN 51511		0W-16
Density at 15°C	DIN 51757	kg/m <sup>3</sup>	843
Viscosity at 40 °C	DIN 51562	mm <sup>2</sup> /s	36,7
Viscosity at 100 °C	DIN 51562	mm <sup>2</sup> /s	7,2
Viscosity index	DIN 2909		164
Pour point	DIN 3016	°C	-48

*Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.*