PRODUCT INFORMATION

oilfino Via Eco V 0W-30



DESCRIPTION

A fuel economy, synthetic motor oil, developed according the most recent technology, based on specially selected synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- · mid SAPS content
- suitable for modern catalysts
- · a very fast cold start
- a safe lubrication film at high temperatures
- extended oil drain intervals
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

APPLICATION

This fuel economy, specially composed motor oil, is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. This motor oil also contributes to the extension of the lifetime of particle filters. Due to its special composition it is possible to apply this product for the VW 504.00/507.00 requirements, in practice also called VW Longlife III.

PERFORMANCE LEVEL

• ACEA C3

Meets the requirements of:

- VW 504.00/507.00
- Porsche C30

| Specific Data | Method | Unit | oilfino Via Eco V 0W-30 |
|-------------------|--------|---------|-------------------------|
| Density at 15 °C | | kg/l | 0,842 |
| Viscosity 40 °C | | mm²/s | 64,00 |
| Viscosity 100 °C | | mm²/s | 12,00 |
| Viscosity Index | | | 178 |
| Flash Point COC | | °C | 202 |
| Pour Point | | °C | -51 |
| Total Base Number | | mgKOH/g | 8,3 |
| Sulphate Ash | | % | 0,78 |

Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.

