PRODUCT INFORMATION

oilfino Via Extra 5W-40



DESCRIPTION

oilfino Via Extra is a synthetic high-performance low friction engine oil for petrol and diesel engines with and without turbocharging. State-of-the-art synthetic technology combined with extremely low cold viscosity and stable high-temperature viscosity ensures significant fuel saving potential.

PROPERTIES

By selectively combining high-quality synthetic components and additives, oilfino Via Extra ensures wear protection and excellent oxidation stability. In addition, the balanced use of additives secures engine cleanliness and helps to prevent formation of black sludge.

SPECIFICATIONS

- ACEA A3/B4
- API SN/CF

PERFORMANCE LEVEL

• MB 229.3

• VW 502.00/505.00

• Porsche A40

• PSA B71 2296

• Opel GM-LL-B-025

• Renault RN0700/0710

• BMW Longlife-01

Specific Data	Method	Unit	oilfino Via Extra 5W-40
SAE grade	SAE J 300		5W-40
Density at 15°C	DIN 51757	Kg/m³	856
Viscosity at 40°C	DIN 51562	mm ² /s	85,3
Viscosity at 100°C	DIN 51562	mm ² /s	14,1
Viscosity index	DIN ISO 2909		171
Flash point	DIN ISO 2592	°C	236
Pour point	DIN ISO 3016	°C	-42
Base number	DIN ISO 3771	mgKOH/g	11,3
Sulphate ash	DIN 51575	g/100g	1,2

Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.

