

oilfino Via Top 10W-40



DESCRIPTION

oilfino Via Top is a semi-synthetic high-performance engine oil for petrol and diesel engines with and without turbocharging. Using synthetic components reduces friction losses in the engine and leads to fuel savings and reduction of negative environmental impact.

PROPERTIES

oilfino Via Top ensures not only wear protection by selectively combining high-quality base oils and additives but also excellent engine cleanliness. Protection against bore polishing helps to avoid excessive oil consumption and the excellent cleaning and sludge carrying capacity prevents formation of black sludge. Low evaporation losses result in avoiding deposit, sludge and varnish and ensure clean pistons as well as piston ring grooves.

SPECIFICATIONS

- ACEA A3/B4
- API SL/CF

PERFORMANCE LEVEL

- MB 229.1
- VW 501.00/505.00
- BMW Special Oil

Specific Data	Method	Unit	oilfino Via Top 10W-40
SAE grade	DIN 51511		10W-40
Density at 15°C	DIN 51757	kg/m ³	873
Viscosity at 40°C	DIN 51562	mm ² /s	94,6
Viscosity at 100°C	DIN 51562	mm ² /s	14,0
Viscosity index	DIN ISO 2909		155
Flash point	DIN ISO 2592	°C	232
Pour point	DIN ISO 3016	°C	-28
Base number	DIN ISO 3771	mgKOH/g	7,9
Sulphate ash	DIN 51575	g/100g	0,95

Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.