

# oilfino Via Ultra FE 5W-30



## DESCRIPTION

**oilfino Via Ultra FE** is a synthetic high-performance low friction engine oil for modern passenger car engines, particularly developed for the latest Ford Group generation with focus on fuel saving potential and reduction of emissions.

## PROPERTIES

Very good pumpability combined with a very low minimum pump temperature ensures excellent cold start properties. A high oil film stability provides protection from wear for the engine, even at high temperature and extreme loads. Excellent viscosity-temperature behaviour combined with significant reduction of friction losses results in fuel savings up to 3%.

## SPECIFICATIONS

- ACEA A5/B5
- API SL/CF

## PERFORMANCE LEVEL

- Ford WSS-M2C913-D

Specific Data	Method	Unit	oilfino Via Ultra FE 5W-30
SAE grade	SAE J 300		5W-30
Density at 15°C	DIN 51757	Kg/m <sup>3</sup>	854
Viscosity at -30°C	DIN 51377	mPAs	4500
Viscosity at 40°C	DIN 51562	mm <sup>2</sup> /s	50,9
Viscosity at 100°C	DIN 51562	mm <sup>2</sup> /s	9,4
Viscosity index	DIN ISO 2909		172
Flash point	DIN ISO 2592	°C	235
Pour point	DIN ISO 3016	°C	-42
Base number	DIN ISO 3771	mgKOH/g	11
Sulphate ash	DIN 51575	g/100g	1,2

*Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.*