

oilfino Via Ultra LL 5W-30



DESCRIPTION

oilfino Via Ultra LL is a synthetic high-performance long-life engine oil for modern car engines, especially developed for fuel saving purposes, considering either standard or extended oil change intervals (up to 50,000 km or 2 years).

PROPERTIES

With its low-emission formulation oilfino Via Ultra LL ensures performing exhaust systems of diesel engines for a very long time and the low sulphur and phosphorus content reduces the load on catalytic converters in petrol engines. Due to very low evaporation losses oil consumption as well as negative environmental impact can be reduced. Very good pumpability even at low temperature ensures best lubrication in the cold running phase. The excellent HTHS (High Temperature High Share) viscosity ensures safe operation of the engine even under extreme loads and high temperature.

SPECIFICATIONS

- ACEA C3
- API SM/CF

PERFORMANCE LEVEL

- VW 504.00/507.00
- MB 229.51
- BMW Longlife-04
- Porsche C30

Please consider prescribed oil change intervals. Not suitable for the following Volkswagen pump/nozzle diesel engines: R5, V10 TDI with and without DPF before 2006. VW standard 506.01 SAE 0W-30 must be used for these engine generations.

Specific Data	Method	Unit	oilfino Via ultra LL 5W-30
SAE grade	DIN 51511		5W-30
Density at 15°C	DIN 51757	kg/m ³	853
Viscosity at -30°C	DIN 51377	mPAs	5950
Viscosity at 40°C	DIN 51562	mm ² /s	66,8
Viscosity at 100°C	DIN 51562	mm ² /s	11,6
Viscosity index	DIN ISO 2909		172
Flash point	DIN ISO 2592	°C	240
Pour point	DIN ISO 3016	°C	-45
Sulphate ash	DIN 51575	g/100g	0,64

Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.